




The 12T is designed to mount on a 2 ton or larger truck. Total pump hoist weight is approximately 8,700 lbs. A deck, headache rack and toolboxes add approximately 3,000 lbs.



Controls are conveniently located at the left rear corner of the machine in close proximity to the work area.

The front portion of the deck remains completely open for cargo.



The tailout winch is used for extending the mast and for tailing out pipe or column, or for pulling submersible pumps. The tailout winch is power-up and power-down. It has a 2,500 lb. lifting capacity at 150 feet per minute and also incorporates a failsafe brake.

#### **Standard specifications**

Maximum mast height: 36 ft.  
Maximum layback: 11 ft.  
Capacity with 3-part line: 33,000 lbs.  
Capacity with single line: 11,000 lbs.  
Mainline cable: 5/8 in. x 150 ft.  
Tailout cable: 3/8 in. x 125 ft.  
Mainline cable speed: 140 ft./min.  
Sandline cable speed: 400 ft./min.  
Hydraulic pump: 3 stage gear

#### **Standard features**

Failsafe brake system  
Direct mounted PTO and pump  
Tailout winch  
Rear outriggers with holding valve  
Holding valve on mast cylinders  
Ring and pinion driven main winch  
Line block  
7 ton and 15 ton hooks  
Controls on left rear corner  
Gray paint

#### **Optional features**

Sandline winch  
Oil cooler  
Cathead  
Breakout wrench  
Front hydraulic outriggers  
Extended mast height  
Custom paint color  
Corded remote control  
Wireless remote control  
Tailgate  
Tool boxes  
Mast lights  
Walking beam  
Other options available upon request



#### **Hunke Manufacturing LLC**

PO Box 128 • Snyder, NE 68664

Phone: 402-568-2221 • Fax: 402-568-2223

E-mail: [sales@hunkemfg.com](mailto:sales@hunkemfg.com) • Website: [www.hunkemfg.com](http://www.hunkemfg.com)