



The 50T has a pulling capacity of 100,000 lbs. The hoist is designed for fast and easy setup by means of a self supporting mast with two 6" bore hydraulic cylinders. A guy cable system is not needed in most situations.



Controls are conveniently located at the left rear corner of the machine in close proximity to the work area.

The front portion of the deck remains completely open for cargo.



Both the mainline and optional sandline use motors that are hydrostatically driven with infinite variable speed control for exceptionally smooth operation. These motors include an internal braking system.

**Standard specifications**

Standard mast height: 44 ft.  
 Standard layback: 6 ft.  
 Capacity with 8-part line: 100,000 lbs.  
 Sandline capacity: 13,000 lbs.  
 Mainline speed: 40 ft./min  
 Sandline speed: 300 ft./min  
 Tailout capacity: 3,000 lbs.  
 Tailout speed: 100 ft./min.

**Standard features**

Internal failsafe brake  
 Oil cooler  
 Tailout winch  
 Rear outriggers with holding valve  
 Holding valve on mast cylinders  
 Line block with hook  
 Controls on left rear corner  
 Gray paint on Mast / Black on deck

**Optional features**

Sandline winch  
 Cathead  
 Breakout wrench  
 Front hydraulic outriggers  
 Custom paint color  
 Electronic walking beam  
 Tailgate  
 Tool boxes  
 Mast lights  
 Other options available upon request



**Hunke Manufacturing LLC**

PO Box 128 • Snyder, NE 68664

Phone: 402-568-2221 • Fax: 402-568-2223

E-mail: sales@hunkemfg.com • Website: www.hunkemfg.com