



Pump Hoist

- Hunke MFG Model S3T
- 9' travel height
- 24' travel length
- 40' mast height
- 360-degree continuous rotation
- Driver side turntable location
- 3,000 lb. single-line lift capacity / 6,000 lb. 2-part line lift capacity
- -10 to +80 degree hoist lift range
- 10' extension/retraction range with
- Estimated 170' per-minute line speed
- Anti 2-block system
- Anti-overload system
- Front stabilizers
- Rear extending H-style street side outrigger & down-only curb side stabilizer
- 4 auxiliary stabilizer pads
- Wireless remote control for boom, turntable & winch functions.
 Secondary manual controls are also provided.
- 120' of 19x7 7/16" cable

- 3 ton Crosby SHUR-LOC hook
- Hydraulic powered tilting enclosed pipe rack (curb side)
- Open cargo area
- Tailgate
- Headache rack
- Rear bumper with hitch receiver

Deck & Compartments

- Hunke MFG heavy-duty sub-structure & cargo area
- Individual aluminum compartments
- Street side compartments One 30"
 W x 58" H x 20" D, one 48" W x 24" H x 20" D, one 24" W x 18" H x 20" D

40'

Curb side compartments - One 30"
 W x 58" H x 20" D, two 48" W x
 24" H x 20" D, one 24" W x 18" H x
 20" D, one 28" W x 15" H x 20" D

Chassis

- 2017 Ford F550 4x4
- 84" CA
- 19,500 GVWR
- Weight: 5,380 lbs. front, 8,800 lbs. rear, 14,180 lbs. gross

Note: The specifications listed refer to the pump hoist and chassis shown in this document. Specifications may very depending on options or modifications.