

R12 Hydraulic Pump Hoist

Capacity with 4-part line: 44,000 lb.

Single line capacity: 11,000 lb.

Mast height: 44 ft.

Standard layback: 10 ft.

When equipped for extra layback: 20 ft.

Main line speed: 120 ft./minute

The optional sandline winch is operated power-up and power-down. It can be switched between 7,000 lbs. bare spool capacity at a maximum speed of 200 feet per minute or 3,500 lbs. capacity at 400 feet per minute.

Sandline cable options:

1,900 ft. of 1/2" cable

2,500 ft. of 7/16" cable

3,400 ft. of 3/8" cable

Standard features

Fail-safe brake system

Direct mounted PTO and pump

Tailout winch

Rear outriggers with holding valve

Holding valve on mast cylinders

Ring and pinion driven main winch

Line block with hook

7 ton and 15 ton hooks

Gray paint

Optional features

Sandline winch

Oil cooler

Cathead

Breakout wrench

Front hydraulic outriggers

Extended mast height

Custom paint color

Remote control

Tailgate

Tool boxes

Mast lights

Other options available upon request



Hunke Manufacturing LLC

PO Box 128 • Snyder, NE 68664

Phone: 402-568-2221 • Fax: 402-568-2223

E-mail: sales@hunkemfg.com • Website: www.hunkemfg.com

