



Fast and easy setup by means of a hydraulically operated self-supporting mast.

The worm gear reduction provides a positive hold on the cable and hook without the need for a winch brake.



Controls are conveniently located at the left rear of the rig so the operator has easy access to the controls and the well head.

A scoping clutch assembly allows the cable and hook to remain stationary as the mast is scoped up and down.



A large portion of the truck bed remains available for storage and hauling of equipment, even in the bed of a 1/2 ton pickup.

Standard specifications

Maximum mast height: 30 ft.
Maximum layback: 6 ft.
Capacity with 2-part line: 2,000 lbs.
Capacity with single line: 1,000 lbs.
Mainline cable: 3/8" x 100 ft.
Mainline cable speed: 75 ft./min.
Winch: Hydraulically drive enclosed worm gear drive

Standard features

Rear outriggers with holding valve
Holding valve on mast cylinder
Hook: 2 ton safety hook
Line block: 2 part line block
Controls on left rear corner
Gray paint

Optional features

Corded remote
Tailgate
Longer outrigger jacks
Electronic speed control
Special paint color
Utility body
Deck
Other options available on request



Hunke Manufacturing LLC

PO Box 128 • Snyder, NE 68664

Phone: 402-568-2221 • Fax: 402-568-2223

E-mail: sales@hunkemfg.com • Website: www.hunkemfg.com